



# CBF SERIES

## ADVANCED DATA SHEET

## DETAILS

**Model Name**

CBF series

**Model Title**

11-50 ton bucket crusher

**Category**

Crushers

**Type**

Bucket

**Brand**

CM

**Description**

The CM CBF Series of crushing buckets are indispensable tools for construction companies, excavator owners, and demolition contractors looking to streamline their operations. These robust attachments fit machines up to 50 tons and excel at on-site material crushing, eliminating the need for transport and disposal costs. With customizable features like jaw adjustment and an optional iron separator kit to remove rebar from your crushed material, these buckets ensure immediate reusability of crushed materials, saving both time and money. Engineered with HARDOX 450 steel for durability and equipped with centralized greasing and a dust suppression kit, the CM CBF Series is designed for optimal performance even in the harshest environments. The CM CBF Series crushing buckets are versatile and can be mounted on a variety of machines, including but not limited to excavators, backhoe loaders, skid steer loaders, and hydraulic system equipped machines. These attachments are suitable for a wide range of construction and demolition environments, offering flexibility and efficiency to meet different operational needs.

## PROCESSED MATERIALS

- Aggregate
- Concrete
- Brick

**RECOMMENDED USE**

<b>Best For</b>	Crushing small amounts of concrete and aggregate directly on site
<b>Good For</b>	Crushing soft rock
<b>Not Built For</b>	Large quantities of aggregate
<b>Best Loader</b>	7 to 50 ton excavators, skid-steer loaders, backhoe loaders, and wheel loaders

**KEY SPECIFICATIONS**

<b>Size In</b>	16" - 20"
<b>Carrier Weight</b>	11 - 50 ton
<b>Jaw Size</b>	(24"x20") - (48"x22")
<b>Max ton per hour</b>	9-17
<b>Operating Weight</b>	3,968 - 11,023 lbs
<b>Size Out</b>	0.4" - 5.5"

**OTHER SPECIFICATIONS**

**Transport Size (L x W x H)** (71"x39"x47") - (83"x63"x53")

**Weight** 3968 - 11023 lbs

**Oil Flow Rate** 32 - 66 gal/min

**Oil Working Pressure** >3190 psi

**Working Size (L x W x H)** (71"x39"x47") - (83"x63"x53")

## FEATURES

- Save money on aggregate:  
Immediately re-use of crushed material on site. Enhances project timelines and cost savings by enabling immediate reuse of crushed materials.
- Durability: Constructed with HARDOX 450 steel for extended longevity.
- Easy and uncomplicated maintenance
- Crushing plates made of a 18% manganese cast for extra strength
- Jaw Adjustment: Allows for customizable output size, ensuring precise material specifications.
- Centralized Greasing: Simplifies maintenance, ensuring smooth operation and reducing downtime.
- Optional Iron Separator Kit: Optional feature to remove rebar and other metals, enhancing material purity.
- Single pressure relief valve and speed regulation
- Control and regulation of hydraulic flow and pressure at the motor inlet
- Full range of attachment sizes and options to fit any machine.
- Suitable for any type of construction site
- Optional Dust Suppression Kit: Minimizes dust generation, improving site safety and environmental compliance.