



# **45 EVO**

## **ADVANCED DATA SHEET**

### **DATA SHEET**





| DETAILS     |  |
|-------------|--|
| Model Name  | 45 EVO   |
| Model Title | Off-road mobile onsite batching plant  |
| Category    | Concrete Batch Plants  |
| Туре        | Mobile   |
| Brand       | Carmix   |
| Description | The CARMIX 4.5 EVO is an all-wheel-drive concrete mixer with self-loading capabilities, designed for high-performance construction projects. It delivers up to 22 yd³ of concrete per hour and is ideal for concrete production in confined spaces. Featuring a 1600-gallon mixing drum and a 158-gallon hydraulic damper-equipped loading bucket, it self-loads your materials to make precise mixes and concrete batches according to preset recipes. Powered by a 129 HP Perkins Turbo Diesel engine, it offers robust performance in diverse conditions with four-wheel drive and an articulated frame for stability and maneuverability. The cabin provides 360-degree visibility and ergonomic controls. |

### PROCESSED MATERIALS

- Cement
- Gravel
- Water

### **DATA SHEET**

45 EVO



| RECOMMENDED USE |  |
|-----------------|--|
| Best For        | Self production and mobile delivery of concrete onsite. On-site production in remote or hard-to-reach locations.                                       |
| Good For        | Avoiding reliance on ready mix schedules, minimum qualities, and leftovers. Projects needing precise mixing and high maneuverability with 4x4x4 drive. |
| Not Built For   | Very high concrete production rates. Projects needing a fixed plant due to space or very high capacity requirements                                    |
| Best Loader     | Self loading - comes with shovel and weight scale  |

| KEY SPECIFICATIONS |                |
|--------------------|----------------|
| Admixtures         | No             |
| Dry/Wet Mixing     | Wet            |
| Yards per hour     | Up to 22 yd³/h |



| OTHER SPECIFICATIONS       |  |
|----------------------------|--|
| Water tank capacity        | Up to 312 gallon                               |
| Speed                      | 5.6-15.5 mph                                   |
| Transport Size (L x W x H) | 19'6" X 7'6" X 13'4"                           |
| Recomended usage           | Self Production                                |
| Max gradient               | 30 %   |
| Batches per hour           | 4  |
| Weight                     | 14,472 lb                                      |
| Tank Capacity              | 34 gallon                                      |
| Engine Power               | 120 hp   |
| Drum Capacity              | 5.8 yd³  |
| Hydraulic tank capacity    | 21 gallon                                      |
| Engine Type                | Perkins diesel engine turbo, STAGE V – TIER 4F |
| Working Size (L x W x H)   | 25'3" X 7'6" X 13'4"                           |



#### **FEATURES**

- Save money on ready mix make your own concrete on site!
- Make more concrete in one batch: 5.8 cubic yard concrete mixing drum (1600 gallons) with double mixing screws and discharge speed independent of engine.
- Drive anywhere: 4x4 power train (4 wheel drive) with automatic hydrostatic transmission
- Save money on fuel: Operates with a remarkably low fuel consumption rate of up to 2.8 gallons per hour
- Front engine with easy maintenance access
- Ergonomic Joymix single joystick operates all main functions.
- Reversible seat with automatic inversion of hydraulic steering circuit
- Water tank 2×156 gallons, diesel 34 gallons, hydraulic oil 21 gallons.
- High quality components such as Bosch-Rexroth transmission, Danfoss hydraulic motors, Perkins Diesel Motor, and Dana Spicer axles
- Increased efficiency, 22 yd3/h with 4 batches per hour
- Self loading shovel with effective capacity per load 158 gallons, complete with hydraulic opening gate
- Slewing and hydraulically tilting chutes, 2 extra chutes included.